

1/1

MKEXCC0048

[www.vieropaints.com](http://www.vieropaints.com)

Viero

CEMENTO



# Cemento

Decorative plaster for “concrete” effect

Description	STONE-CEMENTO is a pre-blended plaster made of water dispersible acrylic resin, micronized inert charges, light stable pigments and specific additives. Recommended for fine decoration of interior walls where a “concrete” effect is desired.
Method of application	<p>Base Coat</p> <ul style="list-style-type: none"><li>after the wall preparation, apply a priming undercoat of VIEROQUARTZ thinned 1:1 in water in the same colour of STONE-CEMENTO. The use of VIEROQUARTZ as a base coat gives an initial coloured covering and protection and facilitates the application of the coating.</li></ul> <p>Steel trowel + sorghum broom/roller + brush</p> <ol style="list-style-type: none"><li>When VIEROQUARTZ is completely dry, apply a uniform layer of STONE-CEMENTO with a small stainless steel trowel all over the surface as base coat</li><li>Once the first coat is dry, apply with the same tool a consistent layer about 3mm thick of STONE-CEMENTO to the wall</li><li>Pass over the surface vertically with a sorghum broom. For a different effect you can also roll over the surface with a wool or rubber roller in a specific texture</li><li>As soon as the plaster is no longer tacky to the touch work across vertically the surface with a blade of stainless steel trowel in a quick sweeping action to smooth the surface. If necessary polish the surface with a fine grain sandpaper</li><li>If desired apply by brush a grout of diluted product (ratio 2:1 with water) adding 5% -10 % of VIERO BITUME DECORATIVO.</li><li>Once dried, smooth and burnish the wall with a soft stainless steel spatula thus breaking the black spots contained in the grout.</li><li>The last step in the STONE-CEMENTO application is the application of the whitening coat. Apply VIEROSIL VEL in a white color (thinned 1:5 with water), by brush all over the surface according to the aesthetic effect required</li><li>Wait until dry and buff it with a dry, clean cotton cloth</li></ol>
Consumption rate	1,7-2,0 Kg/m <sup>2</sup>
Interiors / Exteriors	Interiors

Warning The colours shown are indicative only



CEMENTO - lined effect with Bitume



CEMENTO - scratched effect